



SPECIFICATIONS

L.O.A*:	12.12 m
Length of hull:	11.31 m
Width of hull:	3.77 m
Light displacement EC Version Open/Hard Top:	7070/7470 kg
Air draught:	3.95 m
Draft:	1.10 m
Fuel tank capacity:	650 l
Water tank capacity:	200 l
Maximum engine power:	2 x 220 Kw-2 x 300 HP
Max engine certification:	450 Kw-612 HP
EC certification:	B8 C10

* (with aft swimming platform)

ARCHITECTS

Beneteau Power

DESIGNERS

P. Andreani

PATENT AIR STEP®

R.L. Jeantet - P. Tableau - M. Tronquez

STANDARD EQUIPMENT

CONSTRUCTION

HULL

Technology Air Step®

White hull

Composition: Sandwich (Polyester resin - Glass fibre - Balsa core) - Hull counter moulding laminated in monolithic (Polyester resin - Glass fibre)

7 opening portholes (fitted with curtains)

DECK

Composition: Sandwich (Polyester resin - Glass fibre - Balsa core) - Deck counter moulding laminated in monolithic (Polyester resin - Glass fibre)

DECK EQUIPMENT

Hoop bar (Open version) radar mounting and Bimini top (Options)

Courtesy light in cockpit

Navigation lights

MOORING -ANCHORING

Swivel bow fitting with anchor securing system

Electric windlass (with remote control) 1000W power

2 Forward cleat(s), 2 central and 2 to aft in stainless steel

PERSONNEL GUARDS

Half open pulpit in stainless steel with guardrail and hand rail

2 Stainless steel guard rails on access to catwalk steps

COCKPIT

Self-bailing cockpit - Cockpit cupboard with sink, foldaway tap -

Grill stand (optional extra) and space for cockpit refrigerator

(optional extra) - 7 place outside saloon convertible to sun deck -

Cockpit table in natural solid wood - Space for cased life-raft -

Cockpit shower with mixer tap - Beaker stands and glove box -

Access through a gate with safety catch - Natural solid wood

decked swimming deck with locker for retractable swim ladder

STEERING STATION

Glass windscreen and aluminium and stainless steel frames - Pilot

seat and 2 co-pilot seats with Bolster function - Copilot hand rail -

Compass, fuel gauge and tiller angle indicator - Interior socket 12 V for mobile phone

VERSION HARD TOP

Rigid and non-translucent Hard top in polyester - Electric system with end of trip sensor (open/closed) and switch near to steering station - Glass windscreen with 2 fitted electric wipers

INTERIOR LAYOUT

Wengé type laminated floorboards, light oak and Wengé coloured partitions - Direct lighting (spotlights and indirect lights) - Cushions Paradise Sand

SALOON

Height to deck beam: 1.92 m.

Retractable access door with lock - 4 person sofa - Light oak colour table - CD radio with loudspeakers inside and out - Position intended for television (optional extra), Cubby hole lockers - Large horizontal mirror - 1 Fixed panel in saloon

GALLEY

Height to deck beam: 1.92 m.

Stainless steel sink with mixer tap, 2 hob gas plate - White worktop, cutlery storage - Fridge 80 l, rubbish bin fitted in cupboard

WASHROOM

Height to deck beam: 2.00 m

Marine toilet - Shower curtain - Rigid sewage water tank 80L - Basin with mixer tap - Mirror and storage space - Automatic shower water drainage

OWNER CABIN (FORWARD)

Height to deck beam: 1.90 m.

Wengé type laminated floorboards - Double berth (1.70 m x 2.00 m) - Marine mattress - Closets, spotlights and reading lights. 220 V socket - Space for flat screen TV (optional extra) - 1 Opening hatch fitted with blind

GUEST CABINS (AFT)

Height to deck beam: 1.90 m.

2 Single berths (0.75 m x 1.90 m) - Marine mattress - 1 Opening hatch fitted with blind

ENGINE

Propulsion Stern Drive - **Diesel version Volvo D4 260(2x191 Kw x 2x260 hp) or diesel version Volvo D4 300 (2x221 Kw x 2x300 hp)** - Fuel filter with decanter - Sea water filter - Air intakes on the deck for engine compartment cooling - Hot air extraction forced by electric ventilators
Engine room foam soundproofed
fire extinguishing system activated from the steering station - Fuel filler Stainless steel - 2 Rotomoulded fuel tanks, capacity of 325 L each
Steering system:
Hydraulic steering - 2 Housings with counter rotative propellers

ELECTRIC SYSTEMS

3 Batteries 12 V 110 Ah (2 Engine batteries + 1 Service battery)
- 2 Bilge pumps: 1 Electric pump - 1 Manual pump - 2 Extinguishers - 4 Bilge pumps in petrol version - Inverter 12 V/24 V - Charge divider - Battery charger 12 V 25 Ah - Interior socket(s) 220 V - Shore power 220 V - Spotlight and reading lighting

WATER SYSTEM

Rotational moulded water tank(s), capacity of 200 L - Stainless steel water filler - Water pump for pressurising hot/cold water system
25L water heater working off engine exchanger and 220 V

TRIM LEVEL

	DYNAMIC	AMBITION
Bow thruster + 2 Batteries 12 V 50 Ah	■	■
Spare batteries 1x110 Ah	■	■
40 Amp battery charger instead of 25 Amp charger	■	■
Sun mattress forward Cushions "Columbia"	■	■
Cockpit refrigerator 42L	■	■
Cockpit decked in natural solid wood		■
Quiet Flush electric toilet		■
Multifunction screen RAYMARINE E120 + GPS antenna		■
Loch speedo and sounder transducer		■

OPTIONS

PACKS

PACK ELECTRONIC 2009 +

Auto pilot - Radar 2 Kw24 nm (radome only)

PACK CRUISING

Grill for outside kitchen (with flame guard) - Microwave oven Grill
- TV flat screen 20" + DVD player in the saloon

OTHER AVAILABLE OPTIONS

- Mooring kit (x4), Anchoring (16 kg anchor) and fenders (x6)
- Convertible cockpit top "Dune"
- Aft cockpit closing "Dune"
- Fender storage on pulpit
- White and ruby red two colour hull
- White and steel blue dual colour hull
- Hydraulic bridge Bezensoni
- 2 Electric windscreen wipers (Open version)
- Generator 4 Kva 220 V / 50 Hz power Onan
- Air conditioning Webasto 16 000 BTU 220 V
- Additional double berth in aft cabin
- Glass ceramic cooker table